

1 **Parts to assemble:**
 2 Leg Assembly
 1 Front Panel
 1 Side Support Brace
 4 Carriage Bolt, 2"
 4 Plastic Tee Knob

A. Lay leg assemblies on their sides.
 B. Place front panel on legs.
 C. Braces attach to inside of legs.
 D. Secure with carriage bolts and tee knobs.
NOTE: Leave tee knobs loose on right side.

Front Panel
 Leg Assembly
 Side Support Brace (Fits inside legs.)
 Leave these loose.

Qty. 4
 Qty. 4

NOTE: To prevent scratching, lay grill on packing material to assemble.

2 **Parts to assemble:**
 1 Back Support Brace
 4 Carriage Bolt, 2"
 4 Plastic Tee Knob
 2 Wheel Assembly
 1 Tank Support Bracket
 2 Hitch Pin
 2 Leg Extender

A. Turn assembly upside-down.
 B. Secure back brace and side brace to left leg and back brace to right leg with carriage bolts and tee knobs. **NOTE:** Leave tee knobs loose on right side.
 C. Insert wheel assemblies into legs and bracket. Bracket fits inside legs.
 D. Secure with hitch pin in axle bolt hole closest to leg.
 E. Push leg extenders into right legs.

Wheel Assembly
 Tank Support Bracket
 Leg Extender
 Back Support Brace

Qty. 4
 Qty. 2

3 **Parts to assemble:**
 1 Condiment Basket

A. Stand cart upright.
 B. Place condiment basket hooks over front panel bolts on inside of front leg.
 See inset **A**.
 C. Place condiment basket hooks over back support brace bolts on outside of brace. See inset **B**.
 D. Fully tighten tee knobs on both legs.

Condiment Basket

Qty. 1

4 **Parts to assemble:**
 1 Grill Bottom Assembly
 4 Carriage Bolt, 1/2"
 4 Metal Wing Nut

A. Stand cart upright.
 B. Make sure ignitor wire is connected to ignitor.
 C. Place grill bottom onto supports. Control panel overlaps front panel.
 D. Secure with carriage bolts and wing nuts.

Grill Bottom
 Ignitor Wire
 Control Panel

Qty. 4
 Qty. 4

5 **Parts to assemble:**
 1 V Bar
 1 Cooking Grate

A. Place V bar onto supports at each end of grill bottom.
 B. Place cooking grate onto grill bottom.

Cooking Grate
 V Bar

NOTE:
 Ceramic briquets are not required.

6 **Parts to assemble:**
 2 Side Shelf
 8 Carriage Bolt, 2"
 8 Crown Fasteners

A. Place shelves onto legs (curved edge inward).
 B. Secure with carriage bolts and crown fasteners.

Side Shelf
 Curved Edge

Qty. 8
 Qty. 8

7 **Parts to assemble:**
 1 Grill Lid
 1 Handle Assembly
 2 Metal Wing Nut
 2 Hinge Pin
 2 Hitch Pin
 1 Logo Plate

A. Attach lid to grill bottom with hinge and hitch pins.
 B. Attach handle assembly to lid with two metal wing nuts.
 C. Snap logo plate into grill lid.

Handle Assembly
 Grill Lid (Lid style may vary.)

Qty. 2
 Qty. 2
 Qty. 2

8 **Parts to assemble:**
 1 Warming Rack

A. Slide rear pivot wire of warming rack into holes in grill lid.
 B. Insert leg wires into top hole of three-hole pattern in side of grill bottom.

Warming Rack

Note: Wires at rear of warming rack should point upward.

9 **Parts to assemble:**
 1 Tank Retainer Wire
 1 Carriage Bolt, 1/2"
 1 Plastic Tee Knob

A. Attach retainer wire to left side brace with carriage bolt and tee knob. Leave loose.

Tank Retainer Wire

Qty. 1
 Qty. 1

10 **Parts to assemble:**
 1 LP Gas Tank

LP tank is shipped empty. Fill and leak check before attaching to grill and regulator.

A. Center LP tank on support bracket with collar opening to front.
 B. Slide retainer over tank collar and tighten tee knob.

Tank Collar
 LP Gas Tank

CAUTION
 Tank collar opening must face to front of cart once tank is attached.
 Failure to install tank correctly may allow gas hose to be damaged in operation, resulting in the risk of fire.

See Use & Care manual to perform the "Burner Flame Check" and for important safety instructions before using.

11 **Parts to assemble:**
 1 Grease Clip

A. Hang grease clip beneath grill bottom.
 B. Hang an empty soup can (not included) from grease clip.

CAUTION
 Failure to install can in clip will cause hot grease to drip from bottom of grill with risk of fire or property damage.

Rear view of grill.
 Grease Clip