

1 1st: Unfold legs. Do not stand cart up until front panel is attached. The front panel stabilizes the cart.

Items to Assemble:
 2 Wheels
 1 Tank Support
 2 Axle Bolts
 2 Hitch Pins
 2 Hub Caps

1 Tank Retainer
 1 1-1/4" Carriage Bolt
 1 Wing Nut

2 Control Knobs
 1 Rotary Ignitor

Qty: 1
 Qty: 2
 Qty: 2

Rotary Knob may be attached

1-1/4" Carriage Bolt

Tank Retainer

Wheel attaches in **BOTTOM HOLE** on legs

Tank Support

Hub on wheel faces into leg. Attach in bottom hole on leg with axle bolt and hitch pin.

2

Items to Assemble:
 1 Upper Panel
 4 2" Carriage Bolts
 4 Wing Nuts

1 Lower Panel
 3 2" Carriage Bolts
 3 Wing Nuts

Qty: 7
 Qty: 7

Lower Panel inserts into Upper Panel

Slide Upper Panel under UFC

3 Stand Cart Upright

Items to Assemble:
 1 Left Shelf
 2 3/4" Carriage Bolts
 2 Wing Nuts
 2 Wing Screws

Qty: 2
 Qty: 2
 Qty: 2

View looking down

Insert 3/4" Carriage Bolts into bracket on Legs

Make sure all **four tabs are inside slots** before fastening

4

Items to Assemble:
 1 Sideburner Toolholder
 1 Sideburner
 2 3/4" Carriage Bolts
 4 Wing Screws

Qty: 4
 Qty: 2
 Qty: 2

Underside of shelf and toolholder

View looking down on 3/4" Carriage Bolts

Tabs on toolholder lock into sideburner shelf

5

Item to Assemble:
 1 Condiment Wire
 1 Condiment Tray

A

B

6 1st Remove styrofoam pad

Items to Assemble:
 1 Shield
 2 Tent Frames
 2 Burner Tents
 1 Grate
 1 Griddle

Griddle

Grates

Burner Tent

Tent Frame

Shield

7

Items to Assemble:
 1 Grill Lid
 2 Hitch Pins
 2 Hinge Pins
 1 Logo Plate with clips
 1 Handle
 2 Wing Nuts, Metal

Hinge Pin and Hitch Pin

Qty: 2
 Qty: 2
 Qty: 2

8

Item to Assemble:
 1 Warming Rack

9

Items to Assemble:
 1 Sideburner Grate
 1 Sideburner Knob
 1 Sideburner Wire
 1 LP Tank

LP tank is shipped empty. Fill and leak check before attaching to grill and regulator.

See Use & Care to perform the "Burner Flame Check" and important safety instructions before using.

A Insert Sideburner Tube into Valve and snap valve cup into bottom of shelf. (See inset for proper engagement). Place Sideburner Knob.

B Attach long wire from beneath console to electrode beneath Sideburner.

C Loosen wing nut on tank retainer. Center base of LP tank in notches on the tank support. Lower tank holder onto tank and tighten the wing nut.

IMPORTANT
 Proper tube-to-valve engagement

CAUTION

- Tank collar opening must face to front of cart once tank is attached.
- Failure to install tank correctly may allow gas hose to be damaged in operation, resulting in the risk of fire.

10

Items to assemble:
 1 Chain with Coupling
 1 Match-Holder
 1 Grease Clip

Hang grease clip from center of grill bottom. Use an empty soup can (not included) to hang from grease clip.

CAUTION

• Failure to install can in clip will cause hot grease to drip from bottom of grill with risk of fire or property damage.

See Use & Care Manual for "Match Lighting Instructions"

Place end of chain through hole, reattach coupling to end of chain. Thread eyelet on other end of chain into loop of match holder.

Remove coupling from chain

Eyelet End

Match-Holder