

1 Items to Assemble:
6 Carriage Bolts
6 Wing Nuts

Place Bottom Shelf and Legs as shown.
After assembling tighten all Wing Nuts.

Qty: 6

Qty: 6

Left Side: (Use Upper Hole ONLY) to attach 1 Carriage Bolt and Wing Nut

Right Side: (Use both Upper and Lower Holes) 2 Carriage Bolts and Wing Nuts

2 Items to Assemble:
2 Wheel Assemblies
2 Leg Extenders
2 Hitch Pins

Hitch Pin - Qty: 2

Attach hitch pins to axle rod on wheel assembly after pushing through leg and shelf

3 Items to Assemble:
1 Panel
2 Push Pins
1 Wire Shelf

A. Place tabs into slots on bottom shelf
B. Place wire shelf in 3rd hole from top

Qty: 2

ASSEMBLER NOTE: Assemble front panel first by placing tabs into slots on bottom shelf before inserting wire shelf

4 Items to Assemble:
1 Grill Bottom with Control Panel
1 Heat Shield
4 Carriage Bolts
4 Wing Nuts

Qty: 4

Qty: 4

5 Items to Assemble:
2 Shelves
8 Wing Nut Screws
1 Condiment Basket

Wing Screw -Qty: 8

6 Items to Assemble:
1 Vaporizer Bar

7 Items to Assemble:
1 Grill Lid
2 Hinge Pins
2 Hitch Pins
1 Handle
2 Wing Nuts
1 Logo Plate

Note: Grill lid style may vary.

Qty: 2

Qty: 2

Hinge Pin and Hitch Pin Qty: 2

8 Items to Assemble:
1 Warming Rack
1 Cooking Grate

A Insert pivot wire of Warming Rack into Lid. Flex leg wires to insert into Grill bottom.

B Place cooking grate into grill bottom.

Leg wires on Warming Rack must run underneath surface.

9 Items to Assemble:
1 Grease Clip
1 Tank Wire Support Bracket
1 OPD Gas Tank

USE ONLY WITH AN (OVER-FILL PROTECTION DEVICE) OPD LP TANK

• Hang grease clip from center of grill bottom.
• Use an empty soup can (not included) to hang from grease clip.

CAUTION
• Failure to install can in clip will cause hot grease to drip from bottom of grill with risk of fire or property damage.

LP TANK SOLD SEPARATELY. Fill and leak check before attaching to grill and regulator.
See Use and Care to perform the "Burner Flame Check" and important safety instructions before using.

CAUTION
Tank collar opening must face to front of cart once tank is attached.
Failure to install tank correctly may allow gas hose to be damaged in operation, resulting in the risk of fire.

Rear View of Grill

10

Correct position of LP tank and tank wire support bracket after grill assembly