

**1**

**Parts to assemble:**  
 1 Front Panel  
 2 Side Support Brace  
 4 Carriage Bolt, 2"  
 4 Plastic Tee Knob

A. Lay leg assemblies on their sides.  
 B. Lay front panel on legs.  
 C. Brace side support brace on legs.  
 D. Secure with carriage bolts and tee knobs.

Front Panel  
 Leg Assembly  
 Side Support Brace

Qty. 4  
 Qty. 4

**4**

**Parts to assemble:**  
 1 Grill Bottom Assembly  
 4 Carriage Bolt, 1/2"  
 4 Hex Nut  
 2 Control Knob

A. Stand cart upright.  
 B. Make sure igniter wire is connected.  
 C. Push grill bottom onto supports. Control panel overlaps front panel.  
 D. Secure with carriage bolts and wing nuts.  
 E. Press control knobs onto valves.

Grill Bottom  
 Control Knobs  
 Igniter Wire

Qty. 4  
 Qty. 4

**2**

**Parts to assemble:**  
 1 Back Support Bracket  
 4 Carriage Bolt, 1/2"  
 4 Plastic Tee Knob

A. Turn assembly upside-down.  
 B. Secure back support bracket with carriage bolts and tee knobs.  
 C. Turn assembly right-side-up.  
 D. Secure back support bracket with carriage bolts and tee knobs.

Back Support Bracket  
 Side braces on inside of legs

Qty. 4  
 Qty. 4

**5**

**Parts to assemble:**  
 1 Vapouriser Bar  
 1 Cooking Grate

A. Place vapouriser bar onto the two inner ridges. Vapouriser Bar should rest between the outer support ridges. See inset below.  
 B. Place cooking grate onto grill bottom.

**NOTE:**  
 Ceramic briquettes are not required.

Vapouriser Bar  
 Outer Support Ridges  
 Cooking Grate

**3**

**Parts to assemble:**  
 1 Tank Support Bracket  
 2 Wheel  
 2 Axle Bolt  
 2 Hitch Pin  
 2 Leg Extender

A. Insert axle bolts through wheels, left legs and bracket. Bracket fits inside legs.  
 B. Secure with hitch pins in ends of axle bolts.  
 C. Push leg extenders into right legs.

Wheel  
 Tank Support Bracket  
 Leg Extender

Qty. 2  
 Qty. 2

**6**

**Parts to assemble:**  
 1 Side Shelf  
 5 Carriage Bolt, 2"  
 5 Tee Knobs

A. Place shales onto legs (curved edge inward).  
 B. Secure with carriage bolts and tee knobs.

Side Shelf  
 Curved Edge

Qty. 3  
 Qty. 5

**7**

**Parts to assemble:**  
 1 Grill Lid  
 1 Logo Plate  
 1 Handle  
 2 Hex Wing Nut  
 2 Hinge Pin  
 2 Hitch Pin

A. Attach lid to grill bottom with hinge and hitch pins.  
 B. Attach handle to lid with two metal wing nuts.  
 C. Strap logo plate into lid.

Logo Plate  
 Handle  
 Grill Lid (large way first)

Qty. 2  
 Qty. 2

**8**

**Parts to assemble:**  
 1 SwingAway

A. Slide rear pivot wire of SwingAway into holes in grill lid.  
 B. Insert leg wires into top ends of three-hole pattern in side of grill bottom.

**Note:** Wires at rear of SwingAway should point upward.

SwingAway

**9**

**Parts to assemble:**  
 1 Tank Retainer Wire  
 1 Carriage Bolt, 1/4"  
 1 Plastic Tee Knob

A. Attach retainer wire to left side brace with carriage bolt and tee knob. Leave loose.

Tank Retainer Wire

Qty. 1  
 Qty. 1

**10**

**Parts to assemble:**  
 1 LP Gas Tank

LP tank is shipped empty. Fill and install tank before attaching to grill and regulator.

A. Center LP tank on support bracket with collar opening to front.  
 B. Slide retainer over tank collar and tighten tee knob.

Tank Collar  
 LP Gas Tank

**CAUTION**  
 Tank collar opening must face to front of cart once tank is attached.  
 Failure to install tank correctly may allow gas hose to be damaged in operation, resulting in the risk of fire.

See Use & Care manual to perform the "Burner Flame Check" and for important safety instructions before using.

**11**

**Parts to assemble:**  
 1 Grease Clip

A. Hang grease clip beneath grill bottom.

Grease Clip

Rear view of grill.

**12**

**Parts to assemble:**  
 1 Grease Cup

A. Attach grease cup to grease clip.

Grease Cup

Rear view of grill.

**CAUTION**  
 Failure to install cup in clip will cause hot grease to drip from bottom of grill with risk of fire or property damage.