

**3** **Items to Assemble:**  
 1 Wire Shelf  
 1 Pin  
 2 Push Pins

Assemble front panel by placing tabs into slots on Bottom Shelf. Attach with push pins.

**2** **Items to Assemble:**  
 2 Wheel Assemblies  
 2 Hitch Pins  
 2 Leg Extenders

Attach Wheels with Hitch Pins

**1** **Items to Assemble:**  
 1 Carriage Bolt  
 1 Bottom Shelf  
 6 Carriage Bolts  
 6 Wing Nuts

Place Bottom Shelf and Legs as shown. After assembling tighten all Wing Nuts.

Left Side: Place 1 Carriage Bolt and Wing Nut in upper hole only

Right Side: Attach 2 Carriage Bolts and Wing Nuts in front and back.

**6** **Items to Assemble:**  
 1 Sidesburner Valve Cup  
 1 Carriage Bolt  
 1 Wing Nut  
 1 Wing Screw

Join Sidesburner Body and Frame. Attach with Carriage Bolt and Wing Nut in back, center hole. In front use a Wing Screw to attach Sidesburner Body.

**5** **Items to Assemble:**  
 4 Tie Knobs  
 4 Carriage Bolts

**4** **Items to Assemble:**  
 1 Heat Shield  
 2 Carriage Bolts  
 2 Wing Nuts  
 2 Control Knobs

**9** **Items to Assemble:**  
 1 Grill Lid  
 2 Hinge Pins  
 2 Hinge Pins  
 1 Handle  
 2 Wing Nuts  
 1 Logo Plate

Note: Grill lid style may vary.

**8** **Items to Assemble:**  
 1 V-Bar

Push V-Bar down onto rest in Grill Bottom

**7** **Items to Assemble:**  
 1 Sidesburner  
 1 Wing Nut  
 1 Spring Valve Cup  
 1 Sidesburner Knob  
 1 Sidesburner Grate  
 1 Sidesburner Wire

A Place Sidesburner into hole.  
 B Attach Sidesburner Valve Cup. Make sure Sidesburner Tube is inside of valve. Tighten with Wing Nut.  
 C Place Sidesburner Knob and Grate  
 D Attach long wire from beneath console to electrode beneath Sidesburner.

Correctly assembled Sidesburner Tube in Valve

**10** **Items to Assemble:**  
 1 Warning Rack  
 1 Cooking Grate

A Insert pivot wire of Warning Rack into Lid. Fan leg wires to insert into Grill Bottom.  
 B Place Cooking Grate into Grill Bottom.

Lag wire on Warning Rack must run underneath surface.

**11** **Items to Assemble:**  
 1 Grease Clip  
 1 Grease Clip  
 1 Tank Wire Support Bracket  
 1 LP Tank

Hang grease clip from center of grill bottom. Use the grease clip to hang from grease clip. LP tank is shipped empty. Fill and leak check before attaching to grill and regulator.

**CAUTION**

- Failure to install can in clip will cause hot grease to drip from bottom of grill with risk of fire or property damage.
- Tank collar opening must face to front of cart once tank is attached.
- Failure to install tank correctly may allow gas hose to be damaged in operation, resulting in the risk of fire.

**See Use & Care Manual for "Match Lighting Instructions" and to perform the Burner Flame Check" and Important safety instructions before using.**

**Back of Grill**