WEEKLY MAINTENANCE

Remove scale:

1. Repet steps 1-4 above.
2. Clear the base by partial, fling the base with one 8-oz cup of unditated white vineser, or use Clean-Many²⁰ bibrosers* Let solution stand 20 minutes clearing all the interior surfaces with a soft houst, bancena a doth with unditated white vinegar and wipe out entire base to remove scale.

3. Rises with clean warm water to memore acide and the white white white white white white solutions to be committed to the lot.

Fill water tank with 1 teaspoon of chlorine bleach and 1 gallon of water.

Let the solution stand for 20 minutes, swishing every few minutes. Wet all surfaces.

minutes. Wet all surfaces.

S. Empty the reservoir after 20 minutes, and rinse well with water unit the bleach small is gone. Dry with a clean cloth or paper towel.

4. Check to see if it is time to change the wick filter.

5. Refill the water tank with coch water, replace the humidifier lossing and the water tank. Repeat Operating hearnstones.

STORAGE INSTRUCTIONS

If your humidifier will not be in use for two days or more, or at the end of the season follow these instructions.

Clean and dry the humidifier thoroughly is per the
"Weekly Maintenance" instructions.
Let the humidifier dry completely before storing. Do not
store with water inside the base or water tank.
Remove the tank cap. Do not store with the tank cap in

A HUMIDIFIED SAFFTY PLEASE READ AND SAVE THESE IMPORTANT SAFETY INSTRUCTIONS.

IMPORTANT SAFEGUARDS

IMPORTANT SAFEGUROUS
When using electrical appliances, basic safety precautions should always be followed to reduce the risk of fire, electric shock, and injury to persons, including the following.

1. Read all instructions selone using the appliance.

To avoid fire or snock hazard, plug the appliance directly into a 120V AC electrical outlet. Keep the cord out of heavy traffic areas. To avoid fire hazard, NEVER put the cord under rugs or near heat.

DO NOT place humidifier near heat sources such as

stoves, rediators, and heaters. Locate your humidifier on an inside wall near an electrical outlet. The humidifier should be at least 4" away from the wall for best results. NEVER place humidifier in an area where it is accessible to criddren. NEVER use humidifier in a closed room, particularly where a child may be sleeping, resting, or playing (a closed room may result in excessive humidity).

WARNING: Do not steempt to refit humidifier without first unplugging the unit from its electrical outlet. Failure to freed this warning may cause personal injury. Be sure to unplug the unit by pulling on the plug and not the cord.

Never place anything over moisture outlet when the unit is running.

NEVER drop or insert any object into any openings unless instructed in this manual.

unless restricted in this rimerial.

8. Do NOT open earn an passion with a damaged coal of plag, after the appliance malaritations or at has been dropped or damaged in any manner. Return appliance to immediation, and in manufacture to occurrentation, electrical or 10. been appliance by the interest to economistation and obtained in this manual, Any other use not recommended by the manufacturer of cause file, electric shock, or lightly to persons. The use of attachments not recommended or sold by the immediations are of attachments in the commended or sold by the immediations are one of the commended or sold by the immediations are of cause of the commended or sold by the immediations are of cause to have a file of the commended or sold by the immediations are of cause to have a file of the commended or sold by the immediations are of cause to have a file of the commended or sold by the immediations are of cause to have a file of the commended or sold by the immediation are of cause to have a file of the commended or sold by the immediation are of cause to have a file of the commended or sold by the immediation and the immediation are of the commended or sold by the immediation are of the commended or sold by the immediation are of the commended or sold by the immediation and the commended or sold by the immediation and the immediation and the commended or sold by the immediation and the commended or sold by the immediation and the immediation and the commended or sold by the immediation and the immediation and the commended or sold by the immediation and the immediation are of the immediation and the imm

11 DO NOT use curricors 11.D0 NOT use outdoors.
12.Always place humidifier on a firm, flat, level surface, A waterproof met or pad is recommended for use under the humidifier. NEVER place it on a rug or carpet, or on a first-less floor that may be demaged by exposure.

SERVICE INSTRUCTIONS

Do NOT attempt to repair or adjust any electrical or mechanical functions on this unit. Doing so will world the

mechanical synctrons on this unit. Doing so will void the Warming. The indice of the unit contrision to user sendeable parts. All servicing should be performed by qualified personnel orbit. If you meet no contribution in it is if you meet no exchange the unit, please mit on it in its proportion of the personnel orbit of the personnel orbit you purchased it. If you are returning the unit more than 30 days after the date of purchase, please see the enclosed Warman's.

enclosed Warranty. Should your humidifier require service, please call 1-800-253-2764 in North America for further

assistance.
 If you have any other questions or comments, feel free to write to us or visit our website

Bionaire* JCS/THG, LLC 303 Nelson Avenue Neosho, MO 64850

13. DO NOT allow the Moisture Cutlet to directly face the wall. Missisher could cause damage, particularly to wall paper. 4. Humiofiler should be unplugged when not in use. 15. NEVER this move, or attempt to empty unit while it is operating. Shut off and unplug before removing the water tank and moving the unit.

water tank and moving the unt.

16.This humdlifer requires daily and weekly maintenance to operate appropriately. Refer to disty and weekly cleaning procedures, use only cleaners and additives recommended by the manufacture.

NEVER use detergents, gasoline, glass cleaner, furniture polish, paint thinnes, or other household solvents to clean any part of the humidifier.

clean any part of the humation.

It Excessive humative in a room care cause water concentration on whichever and come furniture. If this concentration on whichever and come furniture. If this concentration is not whichever and come furniture is not an excess of 50%. Use a hypoprometr, available at your in excess of 50%. Use a hypoprometr, available at your ten humative to the humative cause the number of the part of a significant for measurements of the humative companies of the part of a significant of the part of t

21. Never relate transition under water flow or immerse in liquids. 22. Do not plug in the cord with wet hands: electric shock could result.

23, Do not pour water in any openings other than the water

tank.

24. To prevent damage to surfaces, do not place humdifier under overhanging surfaces.

25. NEVER operate unit without water in the tank.

26. Use both hands when carrying full tank of water.

Never unplug unit while it is running as arcing may occur and cause injury. Use power switch to turn off unit before unplugging.

PLEASE READ AND SAVE THESE IMPORTANT SAFETY INSTRUCTIONS

CONSUMER SAFETY INFORMATION

THIS PRODUCT IS EQUIPPED WITH A POLARIZED PLUG WITH A POLARIZED PLUG
(a plug naving one blade wider
then the other). This plag will
not be power outlet or ky one
into the outlet, revise we key. If the plug does not fit fully
into the outlet, revise the plug, If it is still does not fit.
. contact qualified personnel to install the proper outlet.

DO NOT DEFEAT THE SAFETY PURPOSE OF THIS

POLARIZED PLUG IN ANY WAY.

The length of ood used on this appliance was selected to reduce the hazerds of becoming integred in, or highly over a longer court is necessary or approach obtained notations result be equal to or greater than the rating of the humbling-court of the results of the humbling-court of the humbling-cou This device complies with Part15 of the FCC Rules. rins device complex with Part I so that PCC roles. Operation is subjected to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired.

HOW COOL MIST WORKS

FROM COURT MIDS INVOKES.

Your Bloaner' Cool Mist humidifier draws dry air through the riear air intake grill area. This air is their passed through a moisture-feden wick filter, which retains the minerals and deposits in the water. The retaining moist air is directed back into the room from the top air grill. NOTE: This humidification system provides a cool, invisible moisture output, it is normal not to see the mist. NOTE: A humidity level below 20% can be unhealthy and uncomfortable. The recommended humidity level is between 40%-50%.

PRE-OPERATING INSTRUCTIONS

FIRST-UPLIKATIONS INSTRUCTIONS

1. Be sure the humidae is sectical to OFF and the unit is disconnected from the electrical outlet.

2. Salect is location for your hamidiler, or is also surface, about 4" sevey from the well, DO NOT place the humidistry on a shired floor or na hirthme, which can be demagded by moleture or water, Place on a model, respectively.

FILLING THE WATER TANK

FILLING THE WATER TANK

1. Remove the tank from the Housing of the humidifier by grabbing the handle of the tank end pelling floward. All the tank out of the feature, and burgin to the factor, and the state of the feature of the fe

into the housing. There is a tab located on the tank base for easy guidance. The tank holds 1.3 gellons o water. The tank will immediately begin to empty into the base.

3. Plug the power cord into a 120V AC electrical cutlet.

OPERATING INSTRUCTIONS

OPERATING INSTACL TOWN
Your humidilier is equipped with a technologically
advanced Digital Humidistat. You can set the humidilier to
run continuously in manual mode or set the Digital
Humidistat to your desired humidility setting. The Digital
Humidistat will autometically turn the humidifier ON or OFF, depending on the preset comfort level. The comfort level ranges between 35% and 65% relative humidity.

MANUAL MODE INSTRUCTIONS

IAMULAL MODE INSTRUCTIONS

They the humbler into a 130V AC electrical outlet. The display will show the current room humchly. To start the unit, push the MDGOFFF button once for the HGM (3) manual setting.

Pless IbH Usin again for The MEDIUM (2) mensal setting and again for ICM (1). After the selection is made, the display will result no Show the current room reads, the display will result no Show the current room.

humidity.

5. To stop the unit, press and hold the button for two seconds, or keep pressing the button until the display reads OFF (OF).

DICITAL IN IMPOSTAT INSTRUCTIONS

DIGITAL HUMBISTAT INSTRUCTIONS
To take adversely on the Digital Humbistat press the
MCDE/OFF button until the speed is set in either the auto
HCDE/OFF button until the speed is set in either the auto
HCDE/OFF button until the speed is set in either the auto
HCDE/OFF button until HUMBISTATION (MISSING MISSING MISSING

EVTENDED OUR TIME SETTING

EXTEMBED RUN TIME SETTING

By setting you humidfiler to a specific humidity level, you are actually also extending the run time. Since the unit will turn on and off to maintain the set humidity level, less water will be used, so you will need to fill the unit less than you would on manual setting.

USING THE PROGRAMMARI E TIMER

Digital Humidistat allows the user to program the humidifier to come on at a preset time, or turn off after a set amount of time.

SETTING THE OFF TIMER

. Set the mode and/or humidity you wish the humidifier

Set are most accord numbary you was the number to run in.
 While the humanider is number, press and not'd the up and down buttons simultaneously for 2 seconds. The deplay will fish "OO".
 By pressing the up and down buttons, program the humanider to turn off up to 16 hours later in accements.

of 1 hour.

4. After setting the timer, the display will return to show the current room humidity. The timer light will durnisse to show that the firmer is activated.

5. After the predetermined length of time has passed, the humiditer will automatically shat off.

Figure 1

A. Tank B. Tank Handle C. Base D. Humidilier

SETTING THE ON TIMER

PERI ACING THE FILTERS

SETTING THE ON TIMER

1. While the humbillier is off, press and nold the up and down buttons almultaneously for 2 seconds.

2. By pressing the up and down buttons, program the humbillier to turn on up to 15 hours in advance in

numiner to turn on up to go nours in advance in increments of 1 hour.

After the preset length of time has passed, the humidifier will automatically turn on Auto Mode HI at 45% for a preset time of 2 hours.

Through normal use, waterborne minerals and sediment become trapped in the wick filters. The harder your water, the greater the amount of minerals in the water, and the more often you will be able to monitor the life of your siters in your humidilier.

filters in your humidifier. You will be able to monitor the life of the filters in your humidifier by checking the Filter Montter Instante. After 60 minutes of use, Filter Monitor Indicator will move and indicate your filters condition. Now filters will register in the section reading GOOD filter. After frequent use of your humidifier, the Filter Monitor Indicator will let you show when the filters need to be changed See Figure 2).

TO REPLACE THE FILTER, FOLLOW THE STEPS Turn the unit of and disconnect from the electrical outlet.

You when the files need to be changed jose figure. When the needs is the CHANGE section this mers the proper amount of modularie has desting two your air due to the excessive minerals and sediment that have become imposed on your illust. At this point, you should implace you file the proper your proper amount of the proper your files. At the control to obtain sheed performance level.

1. Item the unit of and disconnect from the electrical cubet.
2. Remove the tank from the housing.
3. Unlock the housing from the base by turning the lock knob to the unlocked position.
4. Lift the housing straight up and place to the side.

5. Unlock the wick holder from the base by turning the

. Unlock the wint indicate from the base by unling the look knob to the unlocked position.

Remove the wicks from the wick holder.

Follow the weekly cleaning instructions.

Insert new filters into the wick holder and lock the wick

Insiert new titters into the wick notes and lock the wick holder back onto the base.
 Replace the housing onto the base and lock it into place.
 10.Fit the tank and place back into housing.
 11.Repeat Operating Instructions.
 It will take about 30 minutes for the humidifier to reach.

maximum output.
You can purchase replacement filters (model
8WF100/HF235 – 2 filters) at your local retailer, by calling
1-800-253-2764, filting out the accessory card, or by
visiting www.bicneare.com. it is recommended that a
replacement filter is purchased for uninterrupted use.

CLEANING AND MAINTENANCE INSTRUCTIONS

CLEARING AND MAIN TERRACE UNITABLE TO dry. heated indoor sit. To get the most benefit from the hundifier and avoid product missue, follow all instructions carefully, specifically the operation, care and maintenence guidelines. Please note that this is an electrical appliance, and requires attention when in use.

and requires attention when in use, in addison, if you on not follow the recommended care and maintenance instructions, micro-organisms may be able to grow in the water within the humbilities wester deals to grow in the water within the humbilities were that follow in order to ensure proper, different operation of yout humbilities. Proper maintenance and cleaning a essential to the continued performance of your unit and the modificact of degles or bacterior bankings.

DAILY MAINTENANCE

DAILY MAINTENANCE

1. Se suce the sur is to CFF and is disconnected from the electrical code.

2. Returns the horizoning and the reservoir from the electrical code.

3. Carry the base of the wint to the sine, remove the wides, below a side, can any or entangly water and victors, below a side, can any or entangly water and victors, below a side, can any or entangly water and Virgo bean and dry with a clean cloth or paper towel.

4. Deat the water from the tark in the sale and the paper towel.


5. Put if the submit to the side of the can cloth or paper towel.

6. Put if the submit is the sale and the victor or beau, replaced and the sale and the can cloth or paper towel.

6. Put if the submit is made it the sale and the can cloth or paper towel.

6. Put if the submit is the sale and the sale and the can cloth or paper towel.

6. Put if the submit is the sale and the




or I due repro-to the reploced. or USING MINTO WATER to rand reservoir.

Over 15 favored

Man other is naming

Sea the horderest to a higher or lease secting

ilou nez diegyszin, Power fathre.



TWO (2) YEAR LIMITED WARRANTY

. This Warranty applies only to the original purchaser of this product. A first Windows supples ONEY to require or replacement of any supplied or manufactured parts of this product that upon linguishing by (CSTPI)C, LLC and and the did will not odected in material or workmanship. LSCPIIIC, LLC will observe the version of workmanship. LSCPIIIC, LLC will observe the version of workmanship. LSCPIIIC, LLC will observe the version of the virt. The CSTPIIC consideration of the virt. The contribution of the virt. The vi

the unit, will render this WARRANTY VOID.

D. Unless otherwise proscribed by law, JCS/THG, LLC shall not be liable for any personal injury, property or any incidental or consequential damage of any kind resulting from malfunctions, defects, misuse, improper installation or alteration of this product.

All parts of this product excluding filters, which are covered under separate warranty, are guaranteed for a period of 2 years as follows:

period of 2 years as follows:

1. Within the first 30 days from date of purchase, the store from which you purchased your product should replace this product if it is defective in material or workmarship growthed the store has instock or replacement, it if you intend to essert any claim in connection with the product, plasse follow the instructors in paragraph if.

2. Within the first 24 months from date of

source/OFS in pergiption r.

2. While the first 24 months from date of purchase, JCS/THIG, LLC will repair or replace the product. if it is defected in material or visitimenthy, subject to the conditions in paragraph G.

F. If you have any other problem or claim in connection with this product, please write to our Consumer Service Department.

G, IMPORTANT RETURN INSTRUCTIONS. Your Warranty depends on your following these instructions if you are returning the unit to JCS/THG, LLC: Carefully pack the item in its original carton or other suitable box to avoid damage in shipping.

Before packing your unit for return, be sure to enclose: Your name, full address with zip code and telephone number

b) A dated sales receipt or PROOF OF PURCHASE. SAVE THIS WARRANTY INFORMATION

c) Your \$12.50 check for return shipping and handling, and d) The model number of the unit and the problem.

you are having. (Enclose in an envelope and tape directly to the unit before the box is sealed.)

 JCS/THG, LLC recommends you ship the package U.P.S. ground service for tracking purposes. 4. All shipping charges must be prepaid by you. 5. Mark the outside of your package

Bionaire* JCS/THG. LLC 303 Nelson Avenue Neosho, MO 64850

SHIPPING AND HANDLING CHARGES: \$12.50 (USD) SHEPHING AND HANDLING CHARGES: \$12.20 (USD). This Warranty gives you specific legal rights and you may have other eights which vay firm state to state. The monthcoller of your submitted that the control of the monthcoller of you submitted in the statutory warranties and other rights and remedies contained in any popicable legation. To the exert that any provision of this Warranty's inconsistent with any applicable buy, such providen shall be deemed vided or amended, as

© 2006 ICS/THG, U.C. Bionaire*, the Bionaire logo* and Clean-Away** are trademarks of JCS/THG, U.C.

BCM630CN05EEM1