

This Owner's Manual is provided and hosted by [Appliance Factory Parts](#).



LG HMH009VB Owner's Manual

[Shop genuine replacement parts for LG HMH009VB](#)



[Find Your LG Air Conditioner Parts - Select From 2328 Models](#)

----- Manual continues below -----

Product Specifications (Cooling Only)

Item		Model Name	LS-J0761CL/DL LS-J0763CL	LS-J0962CL	LS-J0821CL LS-J0822AL	LS-J0963CL/AL/DL LS-J0964CL/GL
		Unit				
Cooling Capacity		Btu/h	7,000	9,000	8,000	9,000
Moisture Removal		l/h	1.0	1.2	1.0	1.2
Power Source		Ø, V, Hz	1Ø, 220-240V, 50Hz		1Ø 220V, 60Hz	1Ø, 220-240V, 50Hz
Air Circulation	Indoor	m³/min	5.6	6.7	6.2	6.7
	Outdoor		18	20	18	20
Noise Level	Indoor	dB (A)±3	32	33	32	33
	Outdoor		46	46	46	46
Input		W	690	930	670	920
Running Current		A	2.9	4.1	3.1	4.0
E.E.R.		Btu/hW	10.14	9.7	11.9	9.8
Motor Output	Indoor	W	5	5.7	5	5.7
	Outdoor		14	14.5	14	14.5
Dimensions (W × H × D)	Indoor	mm	802 x 262 x 165			
	Outdoor		525 x 564 x 265			
Net. Weight	Indoor	kg	7			
	Outdoor		20	25	23	23
Refrigerant (R22)		g	440	470	590	530
Airflow Direction Control (Up & Down)			○	○	○	○
Remocon Type			L.C.D Wireless			
Service Valve	Liquid	inch(mm)	1/4" (6.35)			
	Gas		3/8" (9.52)			
Sleeping Operation			○	○	○	○
Drain Hose			○	○	○	○
Connecting Cable			1.0mm²			
Power Cord			1.0mm²			

Product Specifications (Cooling & Heating)

Item		Model Name		LS-J0761HL	LS-J0762HL/HM/HN LS-J0763HL/EL	LS-J0962HL/EL LS-J0964EL
		Unit				
Cooling Capacity	Btu/h			7,000	7,000	9,000
Heating Capacity				7,300	7,300	9,300
Moisture Removal	l/h			1	1	1.2
Power Source	Ø, V, Hz	1Ø, 220-240V, 50Hz				
Air Circulation	Indoor	m ³ /min	5.6	6.4	6.7	
	Outdoor		18	18	25	
Noise Level	Indoor	dB (A)±3	32	32	33	
	Outdoor		46	46	46	
Input	Cooling	W	750	750	900	
	Heating		680	680	870	
Running Current	Cooling	A	3.3	3.3	3.9	
	Heating		3.0	3.0	3.8	
E.E.R.	Cooling	Btu/hW	9.33	9.3	10.0	
C.O.P	Heating		3.14	3.15	3.13	
Motor Output	Indoor	W	5	5	5.7	
	Outdoor		14	14	14.5	
Dimensions (W × H × D)	Indoor	mm	802 x 262 x 165			
	Outdoor		525 x 564x 265	770 x 540 x 245	770 x 540 x 245	
Net. Weight	Indoor	kg	7	7	7	
	Outdoor		21	24	33	
Refrigerant (R22)	g			640	640	590
Airflow Direction Control (Up & Down)			○	○	○	
Remocon Type			L.C.D Wireless			
Service Valve	Liquid	inch(mm)	1/4" (6.35)			
	Gas		3/8" (9.52)			
Sleeping Operation			○	○	○	
Drain Hose			○	○	○	
Connecting Cable			1.0mm ²			
Power Cord			1.0mm ²			