

**1**

Remove end of rating label located on your grill's back panel (see parts list to identify) and apply to your warranty card in box #5. If label cannot be removed, write the numbers on your warranty card.

**OUTDOOR GAS GRILL**  
 © 2011 THE WEBB CORP. CHANDEL, IN 47829  
 Model Number: 000000000  
 Serial Number: 000000000

**NEVER** Store a spare near this barbecue. **NEVER** Fill the tank with propane causing death or occur.  
**NE JAMAIS** remiser u propane sous le grill c  
**NE JAMAIS** remplir la 80%. Un incendie pou, causer des blessures

**DANGER**

This label contains the model and serial number for your grill. You should also write this information on page 2 of your Use and Care Manual in the "Warranty Information" box.

**2**

**1ST** **2ND**

Qty. 4

1. Unfold legs to position shown, laying grill **ON ITS BACK**. Place top of front panel **UNDER** control panel. Rest lower portion of panel on legs, aligning panel holes with leg holes. Leave these loose.

**IMPORTANT:** Top edge of front panel fits UNDER control panel.

2. Attach panel with four bolts and four nuts. **LEAVE NUTS ON RIGHT SIDE LOOSE.**

**NOTE:** To prevent scratching, lay grill on packing material to assemble.

**3**

**1ST** **2ND**

Qty. 4

1. Stand grill upside down and, facing back of grill, attach back panel using two (A) bolts and two nuts on the left, and two (B) bolts, spacer, and two nuts on the right. **LEAVE NUTS ON RIGHT SIDE LOOSE.**

2. Facing back of grill, depress buttons and snap leg extender assembly into right legs and wheel assembly (flex facing inward) into left legs. **IMPORTANT:** Align tabs with notches in legs.

(A) Qty. 2 (B) Qty. 2

Text to inside

Notch

Spacer

BACK PANEL

BACK OF GRILL

**4**

1. Position tank wire with wire ends toward left legs and ends of wire angled upward. Insert ends of wire into holes on inside of left legs and rotate wire downward.

Text to inside

Wire angled upward

Side view

Wire angled upward

Tank wire correctly installed

**5**

1. Place 16 briquets onto briquet grate. Arrange briquets as shown below.

2. Position Drip Vaporiser Bar as shown and place above burner, resting on supports at each end of grill bottom.

Do not let briquets cover burner port holes.

**Briquet Placement**

FRONT BACK

BACK OF GRILL

**1ST** **2ND**

**6**

You may have: Hinge pin only OR Hinge pin and hitch pin

Qty. 2

Qty. 3

1. Place lid onto grill bottom. Attach with two hinge pins.

2. Insert handle into grill lid. Attach with two wing nuts.

3. Be sure clips are attached to logo plate posts. Snap logo plate into grill lid.

4. Place heat indicator into large hole on outside of grill lid. Secure with bracket and wing nut from inside of lid. **DO NOT** overtighten wing nut or bend bracket.

**1ST** **2ND** **3RD** **4TH**

**7**

1. Install condiment basket by placing basket hooks over top bolts on right legs. On rear leg, basket hook must be between spacer and nut. Fully tighten all nuts.

Basket hook

Spacer

Nut

**8**

Back of warming racks pointing upward.

Pivot wire

Leg wire

**1ST** **2ND** **3RD**

1. Insert pivot wire of lower warming rack into lid as shown. Flex leg wires to insert into grill bottom (see inset A).

2. Insert pivot wire of upper warming rack into lid. Flex leg wires to insert into loops of lower rack (see inset B).

3. Place cooking grate into grill bottom.

**9**

1. Install right side shelf by sliding shelf tubes over ends of leg tubes. Press firmly so that holes are aligned. Secure with two push-fasteners.

Qty. 2