

Product Specifications (Cooling Only)

Item	Model Name		7K BTU	9K BTU	11K BTU	12K BTU	14K BTU
	Unit		Cooling Only	Cooling Only	Cooling Only	Cooling Only	Cooling Only
Cooling Capacity	BTU/h(kcal/h)		7,300(1,840)	8,700(2,190)	11,000(2,770)	12,000(3,020)	14,000(3,528)
Moisture Removal	g/h		1.0	1.2	1.2	1.7	1.7
Power Source	Ø, V, Hz		1Ø, 220-240V, 50Hz		1Ø, 220V~,60Hz	1Ø, 220~240V,50Hz	1Ø, 220V~,60Hz
Air Circulation	Indoor	m³/min	4.85	5.3	8.5	10.2	9.5
	Outdoor		25	25	25	25	25
Noise Level	Indoor	dB(A)	36 _i 3	39 _i 3	39 _i 3	41 _i 3	41 _i 3
	Outdoor		47 _i 3	49 _i 3	49 _i 3	50 _i 3	50 _i 3
Input	W		755	920	1,050	1,140	1,270
Runnig Current	A		3.2	4.0	4.9	5.0	5.9
E.E.R.	BTU/h-W		9.7	9.5	10.5	10.5	11
Motor Output	Indoor	W	7	10	10	15	15
	Outdoor		25	25	25	25	25
Dimensions (W x H x D)	Indoor	mm	810 x 220.5 x 152		900 x 290 x 183		
	Outdoor		660 x 540 x 260		801 x 555 x 262		
Net. Weight	Indoor	kg	6.5	6.5	10	10	10
	Outdoor		27	27	33	33	35
Refrigerant(R-22)	g		540	670	1,080	840	980
Airflow Direction Control (Up & Down)			○	○	○	○	○
Remocon type			L.C.D Wireless				
Service valve	Liquid	1/4"(6.35)		1/4"(6.35)			
	Gas	3/8"(9.52)		1/2"(12.7)			
Sleeping Operation			○	○	○	○	○
Drain Hose			○		○	○	○
Connecting Cable			1.0mm²				
Power Cord			1.0mm²				

Product Specifications (Cooling & Heating)

Item	Model Name		7K BTU		9K BTU		12K BTU	
	Unit		Cooling & Heating		Cooling & Heating		Cooling & Heating	
Cooling Capacity	BTU/h(kcal/h)		7,000(1,764)		8,500(2,142)		12,000(3,020)	
Heating Capacity			7,500(1,890)		9,500(2,394)		12,500(3,150)	
Moisture Removal	s/h		1.0		1.2		1.7	
Power Source	Ø, V, Hz		1Ø, 220~240V, 50Hz					
Air Circulation	m³/min		Indoor	4.85	5.3		10.2	
			Outdoor	25	25		25	
Noise Level	dB(A)		Indoor	36 _i 3	39 _i 3		41 _i 3	
			Outdoor	47 _i 3	49 _i 3		51 _i 3	
Input	Cooling	W	760		940		1,250	
	Heating		780		1,030		1,100	
Runnig Current	Cooling	A	3.2		4.1		5.5	
	Heating		3.3		4.0		4.8	
E.E.R.	Cooling	BTU/h·W	9.2		9.0		9.6	
C.O.P	Heating	W/W	2.82		2.7		3.3	
Motor Output	W		Indoor	7	10		15	
			Outdoor	25	25		25	
Dimensions (W x H x D)	mm		Indoor	810 x 220.5 x 152			900 x 290 x 183	
			Outdoor	660 x 540 x 260			810 x 555 x 262	
Net. weight	kg		Indoor	6.5	6.5		10	
			Outdoor	30	30		35	
Refrigerant(R-22)	g		590		690		810	
Airflow Direction Control (Up & Down)			○		○		○	
Remocon Type			L.C.D Wireless					
Service Valve	Liquid		1/4"(6.35)					
	Gas		3/8"(9.52)			1/2"(12.7)		
Sleeping Operation			○		○		○	
Drain Hose			○		○		○	
Connecting Cable			1.0mm²					
Power Cord			1.0mm²					