

This Owner's Manual is provided and hosted by [Appliance Factory Parts](#).



BROAN QTRE090FL Owner's Manual


[Shop genuine replacement parts for BROAN
QTRE090FL](#)



[Find Your BROAN HVAC Parts - Select From 1309 Models](#)

----- Manual continues below -----

MODEL QTRE090FL FAN / LIGHT / NIGHT LIGHT



Ultra-quiet, high performance bath fan / light with a modern-styled grille.

FEATURES

BLOWER:

- Plug-in, permanently lubricated motor - engineered for continuous operation
- Dynamically balanced centrifugal blower wheel for quiet, efficient performance
- Low RPM for quiet operation

HOUSING:

- Rugged, 26 gauge, galvanized steel construction
- Polymeric, 4" duct connector with tapered sleeve and no metallic clatter
- 7-5/8" height allows for 2" x 8" (nominal) joist installations
- Sturdy, easy, four-point mounting directly to joist
- Includes unique spacer (patent pending) for mounting to engineered "I" joists
- Can be mounted in ceilings up to 12/12 pitch

GRILLE:

- Polymeric construction
- Innovative design - the result of extensive research with designers and consumers
- 42W fluorescent lamp* (bulb included)
- 4W night light (bulb not included)
- Durable steel reflector with white enamel finish

CONTROLS (Purchase separately):

- Refer to Broan's catalog for a complete line of accessories to effectively adapt these fans to your construction requirements

U.L. Listed for use over bathtubs and showers when connected to a GFCI protected branch circuit (ceiling mount only).

U.L. Listed for use in insulated ceilings (TYPE I.C.)

California Title 24 compliant.

3-Year Warranty

TYPICAL SPECIFICATION

Ceiling Ventilator shall be Broan Model QTRE090FL.

Ceiling Ventilator shall have corrosion resistant galvanized steel housing with four-point mounting capability. It shall be ducted to a roof or wall cap using 4" round ductwork.

Blower assembly shall be removable, have a centrifugal-type blower wheel and a permanently lubricated motor designed for continuous operation.

Non-metallic damper/duct connector shall be included.

Lamp shall be 42W fluorescent* with separate 4W night light.

Air delivery shall be no less than 90 CFM and sound level no greater than 1.0 Sone. All air and sound ratings shall be certified by HVI.

Ceiling ventilator shall be Energy Star® qualified and have an energy efficient permanent split capacitor motor.

Ceiling Ventilator shall be U.L. Listed for use in insulated ceilings (Type I.C.) and for use over bathtubs and showers when connected to a GFCI protected branch circuit.



* Use only one of the following 42W fluorescent lamps:

| | |
|-----------|---|
| G.E. | F42TBX/835/A/ECO or F42TBX/830/A/ECO or F42TBX/827/A/ECO |
| PHILIPS | PL-T 42W/35/4P/ALTO or PL-T 42W/30/4P/ALTO or PL-T 42W/27/4P/ALTO |
| SYLVANIA | CF42DT/E/IN/835 or CF42DT/E/IN/830 or CF42DT/E/IN/827 |
| NEMA Type | CFTR42W/GX24q/835 or CFTR42W/GX24q/830 or CFTR42W/GX24q/827 |
| Broan | 99271358 |

Broan-NuTone LLC Hartford, Wisconsin www.broan.com 800-558-1711

| REFERENCE | QTY. | REMARKS | Project |
|-----------|------|---------|-------------------|
| | | | Location |
| | | | Architect |
| | | | Engineer |
| | | | Contractor |
| | | | Submitted by Date |

PERFORMANCE RATINGS

MODEL QTRE090FL FAN / LIGHT / NIGHT LIGHT

HVI PERFORMANCE

| Model | Sones @0.1" Ps | CFM @0.1" Ps |
|-----------|-------------------|-----------------|
| QTRE090FL | 1.0 | 90 |



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

AMPS

| Model | Amps * |
|-----------|--------|
| QTRE090FL | 1.0 |

* Total connected load

WEIGHT

| Model | Shipping Weight |
|-----------|-----------------|
| QTRE090FL | 13.6 lbs. |

AIR FLOW PERFORMANCE

MODEL QTRE090FL

