

This Owner's Manual is provided and hosted by [Appliance Factory Parts](http://www.appliancefactoryparts.com).



# SEA BREEZE WA12YMB Owner's Manual

[Shop genuine replacement parts for SEA BREEZE  
WA12YMB](#)



[Find Your SEA BREEZE Air Conditioner Parts - Select From 23 Models](#)

----- Manual continues below -----

# High Efficiency, Quiet Operation and Stylish Compact



# Sea Breeze

## FEATURES:

Multiple Functions - Cooling,  
Dehumidifying & Fan Ventilation

3 Speed Fan Selection -  
Low/Medium/High

Installation Kit with Expandable  
side Panels

Auto Restart (on remote models only)

Retracting Louvers

Window or Through-the-Wall Installation

Slide Out Galvanized Steel Cabinet  
Easy Installation

Protective Rear Grille & Cabinet

Warranty 5 years Compressor 1 year

## Remote Controlled Models

## Manual Controlled Models

	WA12YRB	WA24ZR	WA24ZR	WH12ZM	WH18ZM
<b>BTU COOLING</b>	12000	18000	24000	11600	18000
<b>BTU HEATING</b>	NA	NA	NA	10700	11000
<b>EER</b>	9.8	9.7	8.5	9.8	9.7
<b>DEHUMIDIFICATION (pints/hour)</b>	3.52	4.6	6.5	2.6	4.2
<b>AIRFLOW (CFM)</b>	310	459	618	310	450
<b>VOLTAGE</b>	208/230	208/230	208/230	208/230	208/230
<b>FREQUENCY/cycle</b>	60	60	60	60	60
<b>AMPS COOLING</b>	6.2	12.57	13.1	5.7	8.75
<b>AMPS HEATING</b>	NA	NA	NA	14.84	15.4
<b>WATTS COOLING</b>	1225	1810	2710	1164	1885
<b>WATTS HEATING</b>	NA	NA	NA	3500	3500
<b>PLUG TYPE/NEMA #</b>	Type B/6-15P	Type C/6-20P	Type C/6-20P	Type B/6-20P	Type C/6-20P
<b>POWER CORD RATING/ amps</b>	15	20	20	20	20
<b>POWER CORD TYPE</b>	LCDI	LCDI	LCDI	LCDI	LCDI
<b>POWER CORD LENGTH</b>	4'	6'	6'	6'	6'
<b>REFRIGERANT</b>	R22	R22	R22	R22	R22
<b>REFRIGERANT CHARGE/ Oz.</b>	21.5	27.84	33.44	32.32	27.84
<b>SOUND (INDOOR/OUTDOOR)dba</b>	58/62	56/61	56/61	58/62	59/63
<b>4 WAY AIR ADJUSTMENT</b>	Yes	Yes	Yes	Yes	Yes
<b>2 WAY AIR SWING</b>	Yes	Yes	Yes	Yes	Yes
<b>AIR DISCHARGE</b>	Top	Side	Side	Top	Side
<b>MOTOR TYPE</b>	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing
<b>MOTOR CAPACITOR / mfd</b>	15	7	7	4	7
<b>CONTROLS</b>	Mechanical	Remote	Remote	Mechanical	Mechanical
<b>OPERATING RANGE</b>	64 - 86°F	64 - 86°F	64 - 86°F	64 - 86°F	64 - 86°F
<b>CABINET SIZE/ inches</b>					
<b>Width</b>	22.6	26	26	22.5	26
<b>Depth</b>	21.2	28	30.5	24	28
<b>Height</b>	15.3	17	17	15.5	17
<b>WINDOW OPENING WIDTH</b>	27-38	30-46	30-46	28-44	30-46
<b>THRU WALL MAX THICKNESS</b>	8 3/16	8 1/2	8 1/2	5 1/2	8 1/2
<b>N.W. / G.W lbs.</b>	92/110	150/163	165/183	97/114	150/163
<b>APPROVALS</b>	UL/CUL	UL/CUL	UL/CUL	UL/CUL	UL/CUL

IRP - International Refrigeration Products, 700 Corporate Circle, Toms River, NJ 08755, Phone: 732-736-5699, Fax 732-736-7495, Tec