

High Efficiency, Quiet Operation and Stylish Compact Design

Window units



Sea Breeze

FEATURES:

Multiple Functions - Cooling, Dehumidifying & Fan Ventilation

3 Speed Fan Selection - Low/Medium/High

Installation Kit with Expandable side Panels

Auto Restart (on remote models only)

Retracting Louvers

Window or Through-the-Wall Installation

Slide Out Galvanized Steel Cabinet for Easy Installation

Protective Rear Grille & Cabinet

Warranty 5 years Compressor 1 year parts

Remote Controlled Models

Manual Controlled Models

	WA12YRB	WA24ZR	WA24ZR	WH12ZM	WH18ZM
BTU COOLING	12000	18000	24000	11600	18000
BTU HEATING	NA	NA	NA	10700	11000
EER	9.8	9.7	8.5	9.8	9.7
DEHUMIDIFICATION (pints/hour)	3.52	4.6	6.5	2.6	4.2
AIRFLOW (CFM)	310	459	618	310	450
VOLTAGE	208/230	208/230	208/230	208/230	208/230
FREQUENCY/cycle	60	60	60	60	60
AMPS COOLING	6.2	12.57	13.1	5.7	8.75
AMPS HEATING	NA	NA	NA	14.84	15.4
WATTS COOLING	1225	1810	2710	1164	1885
WATTS HEATING	NA	NA	NA	3500	3500
PLUG TYPE/NEMA #	Type B/6-15P	Type C/6-20P	Type/C6-20P	Type B/6-20P	Type C/6-20P
POWER CORD RATING/ amps	15	20	20	20	20
POWER CORD TYPE	LCDI	LCDI	LCDI	LCDI	LCDI
POWER CORD LENGTH	4'	6'	6'	6'	6'
REFRIGERANT	R22	R22	R22	R22	R22
REFRIGERANT CHARGE/ Oz.	21.5	27.84	33.44	32.32	27.84
SOUND (INDOOR/OUTDOOR)dba	58/62	56/61	56/61	58/62	59/63
4 WAY AIR ADJUSTMENT	Yes	Yes	Yes	Yes	Yes
2 WAY AIR SWING	Yes	Yes	Yes	Yes	Yes
AIR DISCHARGE	Top	Side	Side	Top	Side
MOTOR TYPE	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing
MOTOR CAPACITOR / mfd	15	7	7	4	7
CONTROLS	Mechanical	Remote	Remote	Mechanical	Mechanical
OPERATING RANGE	64 - 86°F	64 - 86°F	64 - 86°F	64 - 86°F	64 - 86°F
CABINET SIZE/ inches					
Width	22.6	26	26	22.5	26
Depth	21.2	28	30.5	24	28
Height	15.3	17	17	15.5	17
WINDOW OPENING WIDTH	27-38	30-46	30-46	28-44	30-46
THRU WALL MAX THICKNESS	8 3/16	8 1/2	8 1/2	5 1/2	8 1/2
N.W. / G.W lbs.	92/110	150/163	165/183	97/114	150/163
APPROVALS	UL/CUL	UL/CUL	UL/CUL	UL/CUL	UL/CUL

