

This Owner's Manual is provided and hosted by [Appliance Factory Parts](#).



Kenmore 79753 Owner's Manual

[Shop genuine replacement parts for Kenmore 79753](#)



[Find Your Kenmore Refrigerator Parts - Select From 665 Models](#)

----- Manual continues below -----



Kenmore Elite 25 cu. ft. Bottom Freezer Refrigerator

- 46-79752 – White
 46-79753 – Stainless
 46-79754 – Bisque
 46-79757 – Black Stainless
 46-79759 – Black

- In-door ice and water dispenser with lockout
- Express fill dispensing technology
- IntelliTouch backlit SmoothTouch™ controls with blue LCD display
- Tilt N Take freezer drawer
- Premium water filtration system
- 2 clear adjustable humidity-controlled crispers
- Full-width, temperature-controlled pantry drawer
- 5 glass shelves (1 space-saving, 4 adjustable split, 3 spill-proof, 3 slide-out)
- 5 door storage bins (2 adjustable gallon)
- Geared freezer drawer rail system
- Tilting freezer drawer basket
- 1 full-width, slide-out freezer basket and 1 full-width, removable slide-out freezer bin
- Adjusta Cube™ ice maker
- 35 3/4" W x 69 3/4" H x 34 1/4" D


Selection	
White	46-79752
Stainless	46-79753
Bisque	46-79754
Black Stainless	46-79757
Black	46-79759
Interior Capacities	
Total Volume (cu. ft.)	24.7
Refrigerator / Freezer Volume (cu. ft.)	17.6 / 7.1
Refrigerator Features	
Fresh Performance	Multi Air Flow
Total Interior Shelves	5 Glass
Adjustable, Split Shelves	4
Spill-Proof, Slide-Out Shelves	3
Space-Saving Shelves	1
Full-Width Pantry Drawer	Temperature-Controlled
Fruit / Vegetable Crisper	2 Clear Adjustable Humidity-Controlled
Egg Bucket / Utility Bin	•
Total Door Shelves / Bins	5 (2 Adjustable)
Gallon Door Storage	2
Covered Dairy Bin	•
Refrigerator Lights	Enhanced LED
Water Filtration and Dispenser	
Water Filtration System	NSF® Certified.
Water Filter Change Indicator	•
Water Filter Location	Up Front
Water Filter Replacement †	46-9990
Through-the-Door Dispenser	with SmoothTouch™ Controls and Blue LCD Display
Express Fill Dispensing Technology	•
Chilled Water	Filtered
Crushed / Cubed Ice	Filtered
Dispenser Lockout	•
Dispenser Light	•
Automatic Night Light	•
Freezer Features	
Drawer / Door Type	Tilt-Out Drawer
Geared Rail System	•
Factory-Installed Ice Maker	Adjusta Cube™
Removable Ice Caddy	•
Fast Ice Production*	Ultra Ice®
Freezer Light(s)	Enhanced LED
Baskets / Bins	1 Full-Width Slide-Out Basket, 1 Full-Width Removable Slide-Out Bin
Freezer Door Shelves / Baskets / Bins	1 Tilt-Out
Frost-Free	Adaptive
General Features	
Up-Front Temperature Controls	SmoothTouch™ (On Dispenser)
Drawer / Bin Color and Accents	Clear
Smooth, Contoured Doors	•
Color-Matched Cabinet / Hinge (All Colors)	•
Hidden Hinges	•
Metal Handles	•
Door Alarm	•
Est. Energy Consumption (kWh / yr.)	547
Est. Yearly Operating Cost**	\$58
Volts / Amps	120 / 15
Shipping Weight (Approx. Lbs.)	366
Warranty	
1 Year Limited Warranty – Entire Appliance	Parts & Labor
2-5 Years Limited Warranty – Sealed Refrigeration System	Parts & Labor

If used for other than private family purposes, warranty applies for only 90 days.

*Increases ice production by 20% in 24 hours

†Replacement filters available at local Sears stores

**All energy \$ / Yr. figures are calculated at the national average cost of / kWh. Energy rebates are offered and paid by the energy supplier in states where such programs exist. Criterion is based on percentage of energy efficiency attained beyond the 2006 standard. Dollar amounts may differ.



A – Height without Hinge
 B – Height with Hinge
 C – Depth without Handle
 D – Depth with Handle
 E – Max. Depth with Doors / Drawer Open
 F – Width

Clearance – Additional Width Required to Open the Doors 90°

Left Hinge – Facing the refrigerator, handle is on your right and hinges are on your left.

Right Hinge – Facing the refrigerator, handle is on your left and hinges are on your right.

Dimensions, Inches	Height		Depth			Width		Clearances	
	A	B	C	D	E	F	Door Edge	Handle	
46-79752	68 3/8	69 3/4	31 3/4	34 1/4	47	35 3/4	1 3/4	4 1/2	

MINIMUM OPENING REQUIRED: When installing next to cabinets, add Width (F) and Door Edge Clearance. When installing next to a wall, add Width (F) and Handle Clearance.

Kenmore exclusive



NSF Certified; the NSF (National Sanitation Foundation) is an independent national agency that establishes standards by which water filtration products are manufactured and tested.

Because of our continuous program of product improvement, Sears reserves the right to change materials and specifications without notice. Consult installation instructions packed with the product for final dimensional data. For complete warranty information, contact your local Sears Commercial Account Manager.

Listed by Underwriters Laboratories



Total volume and shelf area ratings are calculated by the Association of Home Appliances Manufacturers' standards.

46-7975X.PDF
 Effective 03/23/09

Measure Twice...Order Once

Step-by-Step Instructions to Assure You Order the Proper Size Refrigerator

It's Just Good Measure To Double Check Before You Order!

1. Measure the opening for the refrigerator. Don't forget baseboards, molding, tile, countertop overhang, etc. If there is an island in your kitchen, be sure there is enough room to open the door.
2. Refer to the chart for the exact dimensions of the refrigerator.
3. IMPORTANT! Calculate the minimum opening required. When installing next to cabinets, you must allow for Door Edge Clearance. (Multiply Door Edge Clearance by 2 for counter-depth models.) When installing next to a wall, you must allow for the Handle Clearance.
 Adjacent Cabinet: _____ "F" + _____ Door Edge = _____ Min. Opening
 Adjacent Wall: _____ "F" + _____ Handle = _____ Min. Opening
4. Calculate how much the refrigerator will protrude from cabinetry. If the result is undesired, consider a counter-depth model.
 _____ "C" - _____ 24" Cabinet Depth + _____ approx. 2" Electric & Water Connection Clearances = _____ which will Protrude Past Cabinets
5. Measure each door and entry way in the home leading to the kitchen to ensure the refrigerator can be moved through.

