White

Stainless

Bisque **Black Stainless** 

Black

Total Volume (cu. ft.)

Refrigerator / Freezer Volume (cu. ft.)

page 1 of 2

46-79752

46-79754

46-79757 46-79759

24.7

17.6 / 7.1









46-79752 - White


46-79753 - Stainless

46-79754 - Bisque

46-79757 - Black Stainless

46-79759 - Black

- In-door ice and water dispenser with lockout
- · Express fill dispensing technology
- IntelliTouch backlit SmoothTouch™ controls with blue LCD display (6)
- Tilt N Take freezer drawer &
- Premium water filtration system
- 2 clear adjustable humidity-controlled crispers
- Full-width, temperature-controlled pantry drawer
- 5 glass shelves (1 space-saving, 4 adjustable split, 3 spill-proof, 3 slide-out)
- 5 door storage bins (2 adjustable gallon)
- · Geared freezer drawer rail system
- Tilting freezer drawer basket (k)
- 1 full-width, slide-out freezer basket and 1 full-width, removable slide-out
- Adjusta Cube<sup>™</sup> ice maker
- 35 3/4" W x 69 3/4" H x 34 1/4" D



- A Height without Hinge
- **B** Height with Hinge
- C Depth without Handle
- D Depth with Handle - Max. Depth with Doors /
- Drawer Open
- Width

Clearance - Additional Width Required to Open the Doors 90°

Left Hinge - Facing the refrigerator, handle is on your right and hinges are on your left.

Right Hinge - Facing the refrigerator, handle is on your left and hinges are on your right.

Dimensions, Inches	Height		Depth			Width	Clearances	
	Α	В	С	D	Е	F	Door Edge	Handle
46-79752	68 3/8	69 ¾	31 ¾	34 1/4	47	35 ¾	1 3/4	4 1/2

MINIMUM OPENING REQUIRED: When installing next to cabinets, add Width (F) and Door Edge Clearance. When installing next to a wall, add Width (F) and Handle Clearance.





NSE Certified: the NSE (National Sanitation Foundation) is an independent national agence that establishes standards by which water filtration products are manufactured and tested.

Fresh Performance	Multi Air Flow		
Total Interior Shelves	5 Glass		
Adjustable, Split Shelves	4		
Spill-Proof, Slide-Out Shelves	3		
Space-Saving Shelves	1		
Full-Width Pantry Drawer	Temperature-Controlled		
<u> </u>	2 Clear Adjustable		
Fruit / Vegetable Crisper	Humidity-Controlled		
Egg Bucket / Utility Bin	•		
Total Door Shelves / Bins	5 (2 Adjustable)		
Gallon Door Storage	2		
Covered Dairy Bin	•		
Refrigerator Lights	Enhanced LED		
Water Filtration and Dispenser			
Water Filtration System	NSF® Certified.		
Water Filter Change Indicator	•		
Water Filter Location	Up Front		
Water Filter Replacement†	46-9990		
·	with SmoothTouch™ Controls		
Through-the-Door Dispenser	and Blue LCD Display		
Express Fill Dispensing Technology	•		
Chilled Water	Filtered		
Crushed / Cubed Ice	Filtered		
Dispenser Lockout	•		
Dispenser Light	•		
Automatic Night Light	•		
Freezer Features			
Drawer / Door Type	Tilt-Out Drawer		
Geared Rail System	•		
Factory-Installed Ice Maker	Adjusta Cube™		
Removable Ice Caddie	•		
Fast Ice Production*	Ultra Ice®		
Freezer Light(s)	Enhanced LED		
Baskets / Bins	1 Full-Width Slide-Out Basket, 1 Full-Width Removable Slide-Out Bin		
Freezer Door Shelves / Baskets / Bins	1 Tilt-Out		
Frost-Free	Adaptive		
General Features			
Up-Front Temperature Controls	SmoothTouch™ (On Dispenser)		
Drawer / Bin Color and Accents	Clear		
Smooth, Contoured Doors	•		
Color-Matched Cabinet / Hinge (All Colors)	•		
Hidden Hinges	•		
Metal Handles	•		
Door Alarm	•		
Est. Energy Consumption (kWh / yr.)	547		
Est. Yearly Operating Cost**	\$58		
Volts / Amps	120 / 15		
Shipping Weight (Approx. Lbs.)	366		
Warranty			
1 Year Limited Warranty –			
Entire Appliance	Parts & Labor		
2-5 Years Limited Warranty – Sealed Refrigeration System	Parts & Labor		

If used for other than private family purposes, warranty applies for only









<sup>\*</sup>Increases ice production by 20% in 24 hours

<sup>†</sup>Replacement filters available at local Sears stores
\*\*All energy \$ / Yr. figures are calculated at the national average cost of / kWh Energy rebates are offered and paid by the energy supplier in states where such programs exist. Criterion is based on percentage of energy efficiency attained beyond the 2006 standard. Dollar amounts may differ.



page 2 of 2

## Measure Twice...Order Once

Step-by-Step Instructions to Assure You Order the Proper Size Refrigerator

## It's Just Good Measure To Double Check Before You Order!

- 1. Measure the opening for the refrigerator. Don't forget baseboards, molding, tile, countertop overhang, etc. If there is an island in your kitchen, be sure there is enough room to open the door.
- 2. Refer to the chart for the exact dimensions of the refrigerator.
- 3. IMPORTANT! Calculate the minimum opening required. When installing next to cabinets, you must allow for Door Edge Clearance. (Multiply Door Edge Clearance by 2 for counter-depth models.) When installing next to a wall, you must allow for the Handle Clearance.

Adjacent Cabinet: \_\_\_\_\_ "F" + \_\_\_\_\_ Door Edge = \_ Adjacent Wall: \_\_\_\_ "F" + \_\_\_\_ Handle = \_\_\_\_ N \_\_ Min. Opening

4. Calculate how much the refrigerator will protrude from cabinetry. If the result is undesired, consider a counter-depth model. \_ "C" - <u>24"</u> Cabinet Depth + <u>approx. 2"</u> \_ Electric & Water Connection Clearances = \_\_\_\_ \_\_\_ which will Protrude Past Cabinets

5. Measure each door and entry way in the home leading to the kitchen to ensure the refrigerator can be moved through.

