

This Owner's Manual is provided and hosted by [Appliance Factory Parts](#).



Coleman 5999E300 Owner's Manual

[Shop genuine replacement parts for Coleman 5999E300](#)



[Find Your Coleman Camping Parts - Select From 855 Models](#)

----- Manual continues below -----



4D BATTERY QUICKPUMP™



5999E300C


- Inflates AND deflates
- Adaptor works with Coleman® Double Lock™ Valve as well as other airbed valves on the market
- Operates on four D-cell batteries
- Airbed pump only

- Always purchase the correct size and grade of battery most suitable for the intended use.
- Replace all batteries of a set at the same time.
- Clean the battery contacts and also those of the device prior to battery installation.
- Ensure the batteries are installed correctly with regard to polarity (+ and -).
- Remove batteries from equipment which is not to be used for an extended period of time.
- Remove used batteries promptly.


Please call or write us with any comments or questions:
The Coleman Company, Inc.
3600 N. Hydraulic • Wichita, KS 67219 U.S.A.
1 800 835-3278 • TDD: 316 832-8707
www.coleman.com

Manufactured in China


INFLATING COLEMAN® DOUBLE LOCK™ VALVE



To begin inflation, pull firmly on the cap. The internal yellow seal will open internally.



Attach adapter to pump. Insert pump nozzle into the valve.




When fully inflated, stop pumping. The internal yellow seal will close, preventing air from escaping while the cap is removed.



Fully remove the pump adapter. The external cap will appear depressed.

DEFLATION



Remove adapter and attach to deflator. Follow the same steps as in the inflation section to let air out quickly.

**OTHER VALVES:
WORKS WITH STANDARD WIDE OPENING AND BALL BEARING VALVES**

Note: For optimum performance, alkaline batteries are recommended.

Coleman®, , and , are registered trademarks of The Coleman Company, Inc. Double Lock™ are trademarks of The Coleman Company, Inc.