



Please call or write us with any comments or questions



**For products purchased in the United States:**

The Coleman Company, Inc.  
3600 N. Hydraulic  
Wichita, KS 67219 U.S.A.  
1-800-835-3278  
TDD: 1-316-832-8707

**For products purchased in Canada:**

Sunbeam Corporation (Canada) Limited  
DBA Jarden Consumer Solutions  
20B Hereford Street  
Brampton (ON) L6Y 0M1  
1 800 387-6161  
www.coleman.com

© 2009 The Coleman Company, Inc.

Coleman®, , and  are registered trademarks and Quickbed™ is a trademark of The Coleman Company, Inc.

4010005966 (20090615)



## Quickbed™ Airbed with 4D Built-in Pump Instructions

### Valve Operation

#### TO OPEN


##### STEP 1:



Internal Seal Closed

Pull Open Cap.

##### STEP 2:



Fully Opened Valve

Firmly pull cap to unseat valve from inner yellow post.

#### TO CLOSE:

Push to Close 



Internal Seal Closed

Reverse Steps 1 & 2.  
Make sure valve seats on inner yellow post.



Fully Closed Valve

Close Cap.



Quickbed™ Airbed with Built-In 4D Pump



Quickbed™ Airbed with Built-In 4D Pump & Alarm Clock


#### To Set Date, Time & Alarm:

-See the clock instruction in Clock Instruction Manual.



#### To Remove Clock:

-Press on side hinges of clock and remove.



Quickbed™ Airbed with Built-In 4D Pump & MP3 Plug In

#### To Operate:

- Open battery cover and pull jack cord from storage slot.
- Close battery cover, making sure the cord exits the battery cover in the upper, right corner (see Fig. 3).
- Plug cord into headphone jack on any CD player, MP3 player or other audio device.
- Press SPEAKER ON/OFF button to turn on the amplifier.
- Volume is controlled using your device controls, not the pump.

### To Open Battery Cover




Fig.1

- Make sure pump is "OFF" before opening battery cover.
- Press up on latch to open battery cover.




Fig.2

- When using the jack cord, make sure the cord exits the upper, right corner of the battery cover (see Fig. 2) before closing.

### To Insert/Replace Batteries




Fig.3


- Make sure pump is "OFF", then open battery cover (see Fig.1).
- Insert 4 "D" cell batteries as shown. Make sure batteries are installed in the correct orientation following the + and - symbols (see Fig. 3).
- Close the battery cover, making sure it is latched.

**NOTE:** Alkaline batteries are recommended for optimum performance.  
Do not mix battery types.  
Do not mix old & new batteries.


### Inflation/Deflation Instructions

#### 1. Position Airbed

- Unroll and layout airbed in position.
- Make sure the valve is in the closed position (see valve operation).
- Open the battery cover (see Fig. 1).
- Insert 4 "D" cell batteries (not included) into the pump following the + and - labels on the inside of the battery cover.




Control dial in OFF position.




#### 2. Inflate Airbed

- Turn control dial to INFLATE and begin inflation. When bed is fully inflated, turn dial to OFF position.
- To adjust firmness briefly turn control dial: DEFLATE decreases firmness. INFLATE increases firmness.




Turn Control dial to INFLATE position.




#### 3. Deflate Airbed

- Turn the control dial to DEFLATE.
- Once the bed is deflated, turn the control dial to OFF.
- For storage fold the bed and roll it up to store in carry bag.



Turn Control dial to DEFLATE position.



**NOTE:** To conserve battery power, open the valve for primary deflation. Then close the valve and turn the control dial to DEFLATE.