

MODEL COMPARISON

Series	Efficiency (AFUE)	Single Stage	Two-Stage	SureView Window	PSC Motor	Endura Pro Motor	ECM EON Motor	Primary Stainless Steel Heat Exchanger	Secondary Stainless Steel Heat Exchanger	LED Cabinet Lights	Built-in UV Light Air Purifier	Four-Sided Insulated Cabinet	Made In Canada
9700	97%		•	•			•	•	•	•	•	•	•
9600	96%		•	•		•	•		•				•
9600E	95%		•	•			•		•				•
9500	95%	•			•	•			•				•
9200	92.10%	•			•	•			•				•

9600E SPECIFICATIONS

HEATING CAPACITIES	NEV040T2A	NEV060T3A	NEV080T3A	NEV080T4A	NEV100T5A	NEV120T5A
Efficiency (AFUE)	95%	95%	95%	95%	95%	95%
Input (High fire) BTU/hr 0-4500'	38,000	58,000	77,000	80,000	100,000	120,000
Input (Low fire) BTU/hr 0-4500'	26,000	41,000	54,000	56,000	70,000	84,000
CABINET DIMENSIONS (INCHES)	NEV040T2A	NEV060T3A	NEV080T3A	NEV080T4A	NEV100T5A	NEV120T5A
Width (in)	17 1/2	17 1/2	17 1/2	22 1/2	22 1/2	22 1/2
Depth (in)	29 1/2	29 1/2	29 1/2	29 1/2	29 1/2	29 1/2
Height (in)	32 7/8	32 7/8	32 7/8	32 7/8	32 7/8	32 7/8
VENTING *	NEV040T2A	NEV060T3A	NEV080T3A	NEV080T4A	NEV100T5A	NEV120T5A
Clearances to Combustibles	0	0	0	0	0	0
Minimum Vent Size (in)	1 1/2	2	2	2	3	1 1/2
Maximum Vent Size (in)	3	3	3	3	3	2
Minimum Vent Length (ft)	15	15	15	15	15	15
Maximum Vent Length (ft)	100	100	100	100	100	75
AIRFLOW AND COOLING	NEV040T2A	NEV060T3A	NEV080T3A	NEV080T4A	NEV100T5A	NEV120T5A
Motor Type and Size EON	1/3 hp	1/2 hp	1/2 hp	3/4 hp	3/4 hp	1 hp
AC Tonnages	1 1/2, 2, 2 1/2, 3	1 1/2, 2, 2 1/2, 3	2, 2 1/2, 3	3, 4, 5	3, 4, 5	3, 4, 5

*Certified for single or two pipe installation (direct vent)