



# 1-1/2 — 5 Ton 2TTX4018 - 060B

# XL 14i Split System Cooling

## Specifications: 1 Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Mfg. Plant	Shipping Weight
			H	W	D		
2TTX4018B1000A	200/230/1/60	18,000	40	33	30	TY	229
2TTX4024B1000A	200/230/1/60	24,000	40	33	30	TY	245
2TTX4030B1000A	208/230/1/60	30,000	44	33	30	TY	245
2TTX4036B1000A	208/230/1/60	36,000	44	33	30	TY	249
2TTX4042B1000A	208/230/1/60	42,000	46	37	34	TY	292
2TTX4048B1000A	208/230/1/60	48,000	50	37	34	TY	308
2TTX4060B1000A	208/230/1/60	60,000	50	37	34	TY	359

## Accessories:

Model Number	Description	Used With	Mfg. Plant	Shipping Weight
Extended Warranties	(See Extended Warranty Section)			
Controls	(See Control Section)			
AY28X079	Evap. Defrost Control Kit	All Cooling Models	TY	1
TAYASCT501A <sup>①</sup>	Anti-Short Cycle Timer	All Cooling Models	TY	1
BAYKSKT260	Start Kit	2.5 - 4 Ton Models	TY	1
BAYECMT001	Extreme Condition Mounting Kit	All Cooling Models	TY	2
BAYLEGS002	Snow/Sand Legs	All Cooling Models	TY	1
BAYLEGS003	4" Extension	All Cooling Models	TY	1
BAYVDTA003	Vertical Discharge Air Kit Base 3	2 - 3 Ton Models	TY	10
BAYVDTA004	Vertical Discharge Air Kit Base 4	3.5 - 5 Models	TY	10
BAYCCHT301	Crankcase Heater Kit	2.5 - 3 Ton Models	TY	1
BAYISLT101	Rubber Isolators	All Cooling Models	TY	1

<sup>①</sup> Not for use with digital controls.

## Features:

- Climatuff® compressor
- Efficiency up to 15.0 SEER
- All aluminum Spine Fin™ coil
- WeatherGuard™ II top shields unit
- WeatherGuard™ fasteners
- Quick-Sess™ cabinet, service access and refrigerant connections with full coil protection
- DuraTuff™ base, fast complete drain, weather proof
- Comfort"R"™ mode approved
- Glossy corrosion resistant finish
- Internal compressor high/low pressure & temperature protection
- Tarpaulin gray cabinet with anthracite gray top
- Low sound with advanced fan system and compressor sound insulator
- XL Seacoast shield
- 018, 024 & 060 ship with start kit
- Liquid line filter-drier
- Service valve cover
- R-22 refrigerant
- **10 year limited warranty on compressor, coil, and internal functional parts (Residential Use)**
- **Extended warranties available**
- S.E.E.T. design testing
- 100% line run test
- Low ambient cooling to 55°F as shipped
- Low ambient cooling to 30°F with AY28X079

