

1

Parts to assemble:
 2 Leg Assembly
 1 Front Panel
 2 Side Support Brace
 4 Carriage Bolt, 2"
 4 Plastic Tee Knob

A. Lay leg assemblies on their sides.
 B. Place front panel on legs.
 C. Braces attach to inside of legs.
 D. Secure with carriage bolts and tee knobs.

Front Panel

Leg Assembly

Side Support Brace

Qty. 4

Qty. 4

NOTE: To prevent scratching, lay grill on packing material to assemble.

2

Parts to assemble:
 1 Back Support Brace
 4 Carriage Bolt, 2"
 4 Plastic Tee Knob

A. Turn assembly upside-down.
 B. Secure back brace and side braces to legs with carriage bolts and tee knobs.

Side braces on inside of legs.

Back Support Brace

Qty. 4

3

Parts to assemble:
 1 Tank Support Bracket
 2 Wheel
 2 Axle Bolt
 2 Hitch Pin
 2 Leg Extender

A. Insert axle bolts through wheels, left legs and bracket. Bracket fits inside legs.
 B. Secure with hitch pins in ends of axle bolts.
 C. Push leg extenders into right legs.

Wheel

Tank Support Bracket

Leg Extender

Qty. 2

Qty. 2

4

Parts to assemble:
 1 Grill Bottom Assembly
 4 Carriage Bolt, 1/4"
 4 Metal Wing Nut
 2 Control Knob

A. Stand cart upright.
 B. Make sure ignitor wire is connected to ignitor.
 C. Place grill bottom onto supports. Control panel overlaps front panel.
 D. Secure with carriage bolts and wing nuts.
 E. Press control knobs onto valves.

Grill Bottom

Control Knobs

Ignitor Wire

Control Panel

Qty. 4

Qty. 4

5

Parts to assemble:
 1 Vaporiser Bar
 1 Cooking Grate

A. Place vaporiser bar onto the two inner support ridges at each end of grill bottom. Bar should rest between the outer support ridges. See inset below.
 B. Place cooking grate onto grill bottom.

Cooking Grate

Vaporiser Bar

Outer Support Ridge

NOTE: Ceramic briquets are not required.

6

Parts to assemble:
 2 Side Shelf
 8 Carriage Bolt, 2"
 8 Crown Fasteners or Plastic T Knobs

A. Place shelves onto legs (curved edge inward).
 B. Secure with carriage bolts and crown fasteners or T knobs.

Side Shelf

Curved Edge

Qty. 8

Qty. 8

7

Parts to assemble:
 1 Grill Lid
 1 Handle
 1 Logo Plate
 2 Metal Wing Nut
 2 Hinge Pin
 2 Hitch Pin

A. Attach lid to grill bottom with hinge and hitch pins.
 B. Attach handle to lid with two metal wing nuts.
 C. Snap logo plate into lid.

Logo Plate

Handle

Grill Lid (Lid style may vary)

Qty. 2

Qty. 2

8

Parts to assemble:
 1 SwingAway

A. Slide rear pivot wire of SwingAway into holes in grill lid.
 B. Insert leg wires into top hole of three-hole pattern in side of grill bottom.

SwingAway

Note: Wires at rear of SwingAway should point upward.

9

Parts to assemble:
 1 Tank Retainer Wire
 1 Carriage Bolt, 1/4"
 1 Plastic Tee Knob

A. Attach retainer wire to left side brace with carriage bolt and tee knob. Leave loose.

Tank Retainer Wire

Qty. 1

Qty. 1

10

Parts to assemble:
 1 LP Gas Tank

LP tank is shipped empty. Fill and leak check before attaching to grill and regulator.
 A. Center LP tank on support bracket with collar opening to front.
 B. Slide retainer over tank collar and tighten tee knob.

Tank Collar

LP Gas Tank

CAUTION

Tank collar opening must face to front of cart once tank is attached.

Failure to install tank correctly may allow gas hose to be damaged in operation, resulting in the risk of fire.

See Use & Care manual to perform the "Burner Flame Check" and for important safety instructions before using.

11

Parts to assemble:
 1 Grease Clip

A. Hang grease clip beneath grill bottom.

Rear view of grill.

Grease Clip

12

Parts to assemble:
 1 Grease Cup

A. Attach grease cup to grease clip.

Rear view of grill.

Grease Cup

CAUTION

Failure to install cup in clip will cause hot grease to drip from bottom of grill with risk of fire or property damage.