

1

Items to Assemble:

- 6 Carriage Bolts
- 6 Wing Nuts

Place Bottom Shelf and Legs as shown.

After assembling tighten all Wing Nuts.

2

Items to Assemble:

- 2 Wheel Assemblies
- 2 Leg Extenders
- 2 Hitch Pins

3

Items to Assemble:

- 1 Grill Bottom with Control Panel
- 1 Heat Shield
- 2 Carriage Bolts
- 2 Wing Nuts
- 1 Condiment Basket
- 1 Wire Shelf

4

Items to Assemble:

- 2 Shelves
- 8 Crown Nuts
- 8 Carriage Bolts

5

Items to Assemble:

- 1 Vaporiser Bar
- 1 Grate

6

Items to Assemble:

- 1 Grill Lid
- 2 Hinge Pins
- 2 Hitch Pins

7

Item to Assemble:

- 2 Wing Nuts
- 1 Logo Plate
- 1 Handle
- 2 Screws
- 2 Washers

8

Item to Assemble:

- 1 Warming Rack

1. Insert pivot wires into lid (A).
2. Flex leg wires to insert into holes in grill bottom (B).

9

Items to Assemble:

- 1 Grease Clip
- 1 Tank Wire Support Bracket
- 1 LPD Gas Tank
- 1 Tank exclusion shelf

• Hang grease clip from center of grill bottom.

• Use an empty soup can (not included) to hang from grease clip.

CAUTION

• Failure to install can in clip will cause hot grease to drip from bottom of grill with risk of fire or property damage.

LP tank is shipped empty. Fill and leak check before attaching to grill and regulator.

See Use and Care to perform the "Burner Flame Check" and important safety instructions before using.

CAUTION

Tank collar opening must face to front of cart once tank is attached.

Failure to install tank correctly may allow gas hose to be damaged in operation, resulting in the risk of fire.

10

Correct position of LP tank and tank wire support bracket after grill assembly