

1

Items to Assemble:

- 6 Carriage Bolts
- 6 Wing Nuts

Place Bottom Shelf and Legs as shown.

After assembling tighten all Wing Nuts.

Qty: 6

Qty: 6

Left Side: (Use Upper Hole ONLY) to attach 1 Carriage Bolt and Wing Nut

Right Side: (Use both Upper and Lower Holes) 2 Carriage Bolts and Wing Nuts

4

Items to Assemble:

- 1 Grill Bottom with Control Panel
- 1 Heat Shield
- 2 Carriage Bolts
- 2 Wing Nuts

Qty: 2

Qty: 2

7

Items to Assemble:

- 1 Vaporiser Bar
- 1 Grate

Grate Rests

Push Vaporiser Bar down onto rest in Grill Bottom

10

Items to Assemble:

- 1 Grease Clip
- 1 Tank Wire Support Bracket
- 1 LPD Gas Tank

• Hang grease clip from center of grill bottom.

• Use an empty soup can (not included) to hang from grease clip.

CAUTION

• Failure to install can in clip will cause hot grease to drip from bottom of grill with risk of fire or property damage.

LP tank is shipped empty. Fill and leak check before attaching to grill and regulator.

See Use and Care to perform the "Burner Flame Check" and important safety instructions before using

CAUTION

Tank collar opening must face to front of cart once tank is attached.

Failure to install tank correctly may allow gas hose to be damaged in operation, resulting in the risk of fire.

Rear View of Grill

2

Items to Assemble:

- 2 Wheel Assemblies
- 2 Leg Extenders
- 2 Hitch Pins

Hitch Pin - Qty: 2

Attach hitch pins to axle rod on wheel assembly after pushing through leg and shelf

5

Items to Assemble:

- 1 Right Shelf
- 4 Crown Nuts
- 4 Carriage Bolts

Qty: 4

Qty: 4

8

Items to Assemble:

- 1 Grill Lid
- 2 Hinge Pins
- 2 Hitch Pins
- 1 Logo Plate
- 1 Handle
- 2 Wing Nuts

Qty: 2

Qty: 2

Hinge Pin and Hitch Pin

Qty: 2

11

Correct position of LP tank and tank wire support bracket after grill assembly

3

Items to Assemble:

- 1 Panel
- 2 Push Pins
- 1 Wire Shelf

A. Place tabs into slots on bottom shelf

B. Place wire shelf in 3rd hole from top

Qty: 2

ASSEMBLER NOTE: Assemble front panel first by placing tabs into slots on bottom shelf before inserting wire shelf

6

Items to Assemble:

- 1 Sideburner Body
- 1 Sideburner
- 1 Grate
- 2 Wing Nuts
- 2 End Caps
- 1 Sideburner Frame
- 1 Knob
- 1 Carriage Bolt
- 1 Crown Screw

1st:

2nd: Place Sideburner into hole. Insert Valve into Sideburner Tube. Fasten Wing Nut

3rd:

4th:

5th: Locate the long sideburner ignitor wire (attached to ignitor behind control panel). Attach to electrode on bottom of sideburner

Correctly assembled Sideburner Tube in Valve

Qty: 2

Qty: 1

Qty: 1

Sideburner electrode

9

Item to Assemble:

- 1 Warming Rack

1. Insert pivot wires int lid (A).

2. Flex leg wires to insert into holes in grill bottom (B).

(A) Pivot Wire

(B) Flex to insert