

NOTE: If possible, working by 2 or 3 people reduces the risk of injury.

! DANGER
 Never use any kind of metal object (e.g. screwdriver) to adjust the tension of the front panel. The front panel is made of a special material and can be damaged by the use of metal objects.

Do not touch the front panel with your hands. Instead, use the front panel adjustment screw to adjust the tension of the front panel.

NOTE: The front panel is made of a special material and can be damaged by the use of metal objects.

Use the front panel adjustment screw to adjust the tension of the front panel.

NOTE: The front panel is made of a special material and can be damaged by the use of metal objects.

Use the front panel adjustment screw to adjust the tension of the front panel.

10: Do not stand up until front panel is attached. The front panel stabilizes the seat.

Required tools:
 1 Torx screwdriver
 1 Torx screwdriver
 1 Torx screwdriver
 1 Torx screwdriver
 1 Torx screwdriver
 1 Torx screwdriver

Use the front panel adjustment screw to adjust the tension of the front panel.

11: Front Seat Upright

Use the front panel adjustment screw to adjust the tension of the front panel.

12: Back Rest

Use the front panel adjustment screw to adjust the tension of the front panel.

13: Back Rest

Use the front panel adjustment screw to adjust the tension of the front panel.

14: Back Rest

Use the front panel adjustment screw to adjust the tension of the front panel.

15: Back Rest

Use the front panel adjustment screw to adjust the tension of the front panel.

16: Back Rest

Use the front panel adjustment screw to adjust the tension of the front panel.

17: Back Rest

Use the front panel adjustment screw to adjust the tension of the front panel.

18: Back Rest

Use the front panel adjustment screw to adjust the tension of the front panel.

19: Back Rest

Use the front panel adjustment screw to adjust the tension of the front panel.

20: Back Rest

Use the front panel adjustment screw to adjust the tension of the front panel.

21: Back Rest

Use the front panel adjustment screw to adjust the tension of the front panel.

! CAUTION
 Do not touch the front panel with your hands. Instead, use the front panel adjustment screw to adjust the tension of the front panel.

22: Back Rest

Use the front panel adjustment screw to adjust the tension of the front panel.

! CAUTION
 Do not touch the front panel with your hands. Instead, use the front panel adjustment screw to adjust the tension of the front panel.