

1 1st: Unfold legs. Do not stand cart up until front panel is attached. The front panel stabilizes the cart.

Items to Assemble:
 2 Wheels
 1 Tank Support
 2 Axle Bolts
 2 Hitch Pins
 2 Hub Caps
 1 Tank Retainer
 1 1-1/4" Carriage Bolt
 1 Wing Nut, Metal
 3 Control Knobs

Qty: 1
Qty: 2

Wheel attaches in BOTTOM HOLE on legs

Qty: 2

1-1/4" Carriage Bolt

Tank Retainer

Tank Support

Hub on wheel faces into leg. Attach in bottom hole on leg with axle bolt and hitch pin.

2

Items to Assemble:
 1 Upper Panel
 4 2" Carriage Bolts
 4 Wing Nuts
 1 Lower Panel
 3 2" Carriage Bolts
 3 Wing Nuts

Qty: 7
Qty: 7

Lower Panel inserts into Upper Panel

Slide Upper Panel under UFC

3 **Stand Cart Upright**

Items to Assemble:
 1 Left Shelf
 2 3/4" Carriage Bolts
 2 Wing Nuts
 2 Wing Screws

Repeat for Right Shelf
 1 Right Shelf
 2 3/4" Carriage Bolts
 2 Wing Nuts
 2 Wing Screws

Qty: 4
Qty: 4

View looking down

Insert 3/4" Carriage Bolts into bracket on Legs

Make sure all four tabs are inside slots before fastening

4

Item to Assemble:
 1 Condiment Wire
 1 Condiment Tray

A

B

5

Items to Assemble:
 3 Tent Frames
 3 Burner Tents
 2 Grates

Grates

Burner Tents

Tent Frames

6

Items to Assemble:
 1 Grill Lid
 2 Hinge Pin
 2 Hitch Pin

Qty: 2
Qty: 2

Hinge Pin and Hitch Pin

7

Items to Assemble:
 1 Logo Plate
 1 Temp Gauge Bezel
 1 Temperature Gauge w/Wing Nut

8

Items to Assemble:
 1 Handle Assembly
 1 Right Lamp Assembly
 1 Left Lamp Assembly

Note: On the underside of the lamp assemblies are "L" for left side and "R" for right side. Match to letters on the handle.

Attach right and left lamp assemblies to lid with either thumbscrews or Phillips head screws provided. **Do not overtighten screws. Overtightening will cause handle to crack.**

CAUTION: To prevent a shorting condition make sure the lamp assemblies are fully inserted into casting.

INCORRECT ASSEMBLY

CORRECT ASSEMBLY

Left

Right

or

or

9

Items to Assemble:
 1 Chef's Delite
 2 Swing Grid Bolts
 2 Wing Nuts, Metal

Qty: 2

10

Items to Assemble:
 1 LP Tank (purchased)
 1 AAA Battery

A Loosen wing nut on tank retainer. Center base of LP tank in notches on the tank support. Lower tank holder onto tank and tighten the wing nut.

B Place "AAA" battery into module, secure with button.

Button

Battery

CAUTION

- Tank collar opening must face to front of cart once tank is attached.
- Failure to install tank correctly may allow gas hose to be damaged in operation, resulting in the risk of fire.

11

Items to assemble:
 1 Chain with Coupling
 1 Match-Holder
 1 Grease Clip
 1 Grease Cup

Hang grease clip from center of grill bottom. Use an empty soup can to hang from grease clip.

CAUTION

• Failure to install can in clip will cause hot grease to drip from bottom of grill with risk of fire or property damage.

See Use & Care Manual for "Match Lighting Instructions"

Place end of chain through hole, reattach coupling to end of chain. Thread eyelet on other end of chain into loop of match holder.

Remove coupling from chain

Eyelet End

Match-Holder

Back of Grill

Grease Clip

Grease Cup